

CRAWLER EXCAVATOR ZE20G

| | Items | ZE20G |
|----------------------------|------------------------------------|----------------------|
| Basic Technical Data | Operating Weight | 1970 kg |
| | Standard bucket capacity | 0.04 m³ |
| | Slewing Speed | 9.5 r/min |
| | Traveling Speed(high/low) | 4.2/2.2 km/h |
| | Max. Drawbar Pull | 16.6 kN |
| | Digging Force of Bucket | 18 kN |
| | Digging Force of Stick | 8.5 kN |
| Engine | Engine Manufacturer | Kubota |
| | Engine Model | D1105 |
| | Rated Power | 15.4 kW / 2400 rpm |
| | Displacement | 1.123 L |
| | Emission Standard | EU Stage V / Tier 4F |
| Dimensions | Length | 3885 mm |
| | Width | 980/1300 mm |
| | Height | 2310 mm |
| | Boom Length | 1830 mm |
| | Stick Length | 1190 mm |
| | Tail Slewing Radius | 1100 mm |
| | Track Gauge | 750/1070 mm |
| | Length of Track On Ground | 1240 mm |
| Operating Range | Max. Digging Reach | 4130 mm |
| | Max. Digging Reach at Ground Level | 4070 mm |
| | Max. Digging Depth | 2555 mm |
| | Max. Digging Height | 3630 mm |
| | Max. Dumping Height | 2550 mm |







